



PCB影像整合
自動化設備

AUTO SCREEN TENSION M/C

CHPN-2000



Feature/Function:

Suitable: each kind yarns spread process

Suit produce high precision PCB frame. super high precision LCD frame & PDP frame, spread capacity about 4~8pcs/1hour (cost time is different depend on precision or process, this machine is the highest level auto spread machine in the produce auto spread machine group.

Option:

1. This device suit each kind yarns, can reduce people miss by a side margin, reduce cust and increase produce capacity.
2. Using auto system with out people educate, training...etc problems. Machine breakdown can repair easily and don't consume time.
3. This machine owns special spread function & tension set up auto compensate function. Using for special spread ang overcome pulling out of balance & scripture, woof yarn winding make printing be out of shape....etc problems.
4. Any step during auto spreading, can adjust tension set up range, save files after measure pulling until finish data or spreading directly to produce.
5. Within 20 groups set up for choosing, can revise, save by self (save files must input password, password can change by self, total are 4 words), supply user to change yarn quickly.
6. Spread speed using independence way, depend on demands can change anytime (ex: the most thin yarn need speed slowly.), there are 1~15 parts owns locked function, prevent over push down to make the range changed.
7. Self-support frame rise up auto adjustable function, suitable 20mm~50mm frame, can adjust gap between frame and yarn, without adjusting height to match frame by hand.
8. Using Germany original special vacuum motor, excluding spread gum's rare delicacy ang solidify accelerate, Increase produce capacity.
9. The frame gum's dry time can set up without restriction. When dryness time in up will auto relax tension, stopping vacuum.
10. Operating interface high cleverness, can 360° turn round and owns fix function. Operating are smoothly.

Spec.:

01	spread speed	1~15 part speed set up	07	air consumption	5~6kg 10Liter/min
02	spread angle	0°~16°	08	voltage	3Ø220V/380V, 50~60Hz, 1KW, 4A
03	Highest pulling force	60newton	09	M/c weight	1550kg
04	frame height	20mm~50mm	10	spread error range	±0.5newton
05	spread capacity	4~8pcs/1hour	11	yarn size	1360*1360mm
06	M/c dimension	2050X2035X1255(mm)	※	Changing design depended on customer's special yarn size	

景暉精密企業有限公司 CHING HUEI PRECISION CO., LTD.

臺灣總公司

公司電話: 886-3-3222845-6

公司傳真: 886-3-3228325

公司地址: 338桃園蘆竹鄉南崁路一段305號

(臺灣)E-mail信箱: fa0325@ms18.hinet.net

工廠電話: 886-3-3522894

工廠地址: 338桃園蘆竹鄉南崁路一段349巷19號

統一編號: 31345346

(臺灣)E-mail信箱: ch_data@chinghueiweb.com

中國區客戶服務點

(華南) 東莞市長安景暉機械貿易部

地址: 中國廣東省東莞市長安鎮銘恩西街10巷1號

電話: 86-769-85393616, 85393627 傳真: 86-769-85393621

郵箱: chyjsl@china3721.com

(華東) 蘇州服務處

蘇州市新區濱河花園30幢305室

電話: 86-512-68785262 傳真: 86-512-68249272

郵箱: zhuyilongsu@163.com

(業務&客訴)E-mail信箱: chinghuei@changnan.net

公司網頁: <http://www.chinghueiweb.com>